

DATA SHEET

EMB01S-CIO

ABB Ability™ Symphony® Plus Hardware Selector



The EMB01S-CIO Evolution Module Base provides the mounting of an AD11e Analog Drive module to an EMC-_B0x Evolution Mounting Chassis. The base connects the I/O module to the HN800 I/O bus and the I/O cable to the field termination.

The base supports all of the functions of the AD11e module. This includes HART on the Analog I/O, SOE timestamping on digital inputs, and optional I/O module redundancy.

Features and benefits

- Mounts AD11e to EMC-_B0x Evolution Mounting Chassis
- Connects AD11e to redundant HN800 I/O bus
- Connects AD11e to NTCS04 TU via NKTU01 cables
- Connects AD11e to NICS01 TM via NKTU02 or NKTM01 cables
- Mounts AD11e to EMC-_B0x Evolution Mounting Chassis
- Connects AD11e to redundant HN800 I/O bus
- Connects AD11e to NTCS04 TU via NKTU01 cables
- Connects AD11e to NICS01 TM via NKTU02 or NKTM01 cables

General info		
Article number	7PAA005092R11	
Life cycle status	Active	
Line redundancy	Yes	
Channels	13	
Hot swap	No	
Supported IO modules	AD11e	
Singular or redundant	Singular	
Form factor	EMCB0_ Evolution Mounting Chassis	
Mounting	EMC-DB01, EMC-DB02, EMC-SB01, EMC-SB02	
HN800 bus length	190 mm	
MTBF (per MIL-HDBK-217-FN2)	PR C: 1,384,953 Hours @ 30 ° C, 1,350,557Hours @ 40 ° C, 1,231,591 Hours @ 70 ° C	
MTTR (Hours)	8 Hrs	

Detailed data		
Overvoltage category	Category 1 for power. Tested according to IEC/EN 61010-1	
Process signal connections	Thirteen (13) Total: 4-AI, 2-AO, 3-DI, 4-DO	
Field power connection	Thirteen (13) Total: 4-AI, 2-AO, 3-DI, 4-DO	
Field power fusing	@ I/O Termination (TU or TM)	
Signal connection	Terminable Blocks on NTCS04, NICS01 or HDIOT-CIO-01	
Max current	250 mA	
Galvanic isolation test voltage	1500 V for up to 1 minute	

Environment and certification		
Temperature, Operating	-40 to +70 °C Tested according to IEC/EN 60068-2-1, IEC/EN 60068-2-2	
Temperature, Storage	-40 to +85 °C Tested according to MIL-STD-810G	
Relative humidity	20% to 95% @ 40°C non-condensing. Tested according to IEC/EN 60068-2-78, IEC/EN 61298-3	
Vibration (operational sinusoidal)	5 to 60 Hz 0.137 mm (0.0054 in.), 60 to 150 Hz 1.0 G. Tested according to IEC/EN 60068-2-6	
Vibration (transportation)	10 to 500 Hz. Tested according to MIL-STD-810G	
Shock (storage)	15 G, 11 msec. Tested according to IEC/EN 60068-2-27	
Drop	100 mm. Tested according to IEC/EN 60068-2-31	
Protection class	IP20 according to EN 60529	
Altitude (operational)	Sea level to 3,048 meters (10,000 ft.) Tested according to MIL-STD-810G	
Altitude (storage)	Sea level to 12,192 meters (40,000 ft.) Tested according to MIL-STD-810G	
Air quality	ISA S71.04 G3 compliant	
ESD immunity	Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-2, Severity level 3	
Surge immunity	Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-5, Severity level 3	
Electrical fast transient immunity	Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-4, Severity level 3	
Radiated RFI immunity	Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-3, Severity level 3	
Conducted Immunity	Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-6, Severity level 3	
Magnetic field immunity	Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-8, Severity level 4	
Radiated emission	Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-6, Severity level 3	
Conducted emission	Tested according to IEC/EN 61000-6-4, CISPR 11 + A1, CISPR 16-1-1, Group 1, Class A, ISM equipment	
Voltage dips and interruption immunity	Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-11	
CSA non-hazardous locations	Certified for use as process control equipment in an ordinary (non-hazardous) location	
CSA hazardous, nonincendive locations	Class I, Division 2, Groups A, B, C, D	
CE Mark	CE Mark EMC directive 2004/108/EC & Low Voltage Directive 2006/95/EC	
RoHS compliance	RoHS Directive 2015/863	
WEEE compliance	DIRECTIVE/2012/19/EU	

Dimensions		
Width	35.5 mm	
Depth	173.46 mm	
Height	177 mm	
Weight	204 g	



solutions.abb/symphonyplus solutions.abb/controlsystems

800xA and Symphony Plus is a registered trademark of ABB. All rights to other trademarks reside with their respective owners.

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2025 ABB All rights reserved