

MBA-SM01

ABB Ability™ Symphony® Plus Hardware Selector



The MBA-SM01 Mounting Base Adapter is used to mount an SDe Series I/O Module to 'Full-Size' SD Series Singular Module bases. The adapter enables SDe Series I/O modules to be used to replace Singular, 'Full-Size' SD Series I/O modules .

Features and benefits

- The MBA-SM01 Mounting Base Adapter enables the following use cases where SDe Series I/O modules replace SD Series Singular I/O Modules:
- AD11e module replacing an AD01, AD02, or AD11 module mounted in a _BS01-EPD base
- AI12e/FI12e module replacing an AI01 or AI02 module mounted in a _BS01-EPD or _BS0-FPH base
- AO02e module replacing an AO01 or AO02 module mounted in a _BS01-EPD base
- AX05e module replacing an AI05 or AO05 module mounted in a _BS01-EPD base
- DI06e module replacing a DI01, DI02, DI03 or DI04 module mounted in a _BS01-EPD, _BS01-FPH, or _BS01-FPN base
- DO01e module replacing a DO01 module mounted in a _BS01-EPD, _BS01-FPH, or _BS01-FPN base
- DO02e module replacing a DO02 module mounted in a _BS01-EPD, _BS01-FPH, or _BS01-FPN base
- DO05e module replacing a DO05 module mounted in _BS02-EPD base @ .5 Amp Max
- PI01e module replacing a PI01 module mounted in a _BS01-EPD, _BS01-FPH, or _BS01-FPN base

General info	
Article number	7PAA008655R11
Line redundancy	Redundant HN800 I/O Bus
Channels	16
Hot swap	No
Supported IO modules	AD11e, AI12e, AO02e, DI06e, DO01e, DO05e, FI12e, PI01e
Singular or redundant	Singular
Form factor	SD Series 'Full-size'
Mounting	SD Series DIN-Rail Bases
HN800 bus length	50 mm
MTBF (per MIL-HDBK-217-FN2)	PR A: 9,121,503 hours @ 30 °C 7,937,322 hours @ 45 °C 5,385,604 hours @ 70 °C
MTTR (Hours)	24 Hrs

Detailed data	
Overvoltage category	Category 1 for power. Tested according to IEC/EN 61010-1
Process signal connections	Up to 16 Analog or Digital I/O Channels, Dependent on I/O Module Type
Field power connection	none
Field power fusing	n/a
Signal connection	Adapter
Max current	.5 Amps
Acceptable field signal wire sizes	n/a
Galvanic isolation test voltage	1500 V for up to 1 minute

Environment and certification	
Temperature, Operating	-40 to +70 °C Tested according to IEC/EN 60068-2-1, IEC/EN 60068-2-2
Temperature, Storage	-40 to +85 °C Tested according to MIL-STD-810G
Relative humidity	20% to 95% @ 40 °C non-condensing. Tested according to IEC/EN 60068-2-78, IEC/EN 61298-3
Vibration (operational sinusoidal)	5 to 60 Hz 0.137 mm (0.0054 in.), 60 to 150 Hz 1.0 G. Tested according to IEC/EN 60068-2-6
Vibration (transportation)	10 to 500 Hz. Tested according to MIL-STD-810G
Shock (storage)	15 G, 11 msec. Tested according to IEC/EN 60068-2-27
Drop	100 mm. Tested according to IEC/EN 60068-2-31
Protection class	IP20 according to EN 60529
Altitude (operational)	Sea level to 3,048 meters (10,000 ft.) Tested according to MIL-STD-810G
Altitude (storage)	Sea level to 12,192 meters (40,000 ft.) Tested according to MIL-STD-810G
Air quality	ISA S71.04 G3
ESD immunity	Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-2, Severity level 3
Surge immunity	Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-5, Severity level 3
Electrical fast transient immunity	Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-4, Severity level 3
Radiated RFI immunity	Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-3, Severity level 3
Conducted Immunity	Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-6, Severity level 3
Magnetic field immunity	Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-8, Severity level 4
Radiated emission	Tested according to IEC/EN 61000-6-4, CISPR 11 + A1, CISPR 16-1-1, Group 1, Class A, ISM equipment
Conducted emission	Tested according to IEC/EN 61000-6-4, CISPR 11 + A1, CISPR 16-1-1, Group 1, Class A, ISM equipment
Voltage dips and interruption immunity	Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-11
CSA non-hazardous locations	Certified for use as process control equipment in an ordinary (non-hazardous) location
CSA hazardous, nonincendive locations	Class I, Division 2, Groups A, B, C, D
CE Mark	CE Mark EMC directive 2004/108/EC & Low Voltage Directive 2006/95/EC
RoHS compliance	RoHS Directive 2015/863
WEEE compliance	DIRECTIVE/2012/19/EU

Dimensions

Width	26.76 mm
Depth	54.9 mm
Height	189.8 mm
Weight	120 g

solutions.abb.com/symphonyplus
solutions.abb.com/controlsystems

800xA and Symphony Plus is a registered trademark of ABB. All rights to other trademarks reside with their respective owners.

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2025 ABB All rights reserved